

# Talk **PRO**<sup>™</sup> **X-10**

**ANALOG  
TWO-WAY  
RADIO**



## **Recommended For**

- **Railways (General Purpose)**
- **Shops**
- **Construction Sites**
- **Security Services**
- **Shop Floors**
- **Spots, Events**
- **Wedding Planners**
- **Videographers**

Talk PRO X-10 is a cost-effective analog two-way radio designed for the **Indian marketplace**. Delightfully small and compact, with a comprehensive analog feature kit that includes **Squelch Levels, Auto Power Save, Low Battery Alert, Monitor, BCL, TOT and CTCSS/CDCSS**, this walkie talkie is curated to deliver convenience and efficiency at a **budget friendly pricetag**.

# Talk **PRO**<sup>™</sup> X-10

## MAIN FEATURES



Auto Power Save



Squelch Levels



Anti-Slip Design



Low Battery Voice Alert



**MIL - STD - 810**

**Ingress Protection Class IP54**

**VOX (Voice Operated Switch)  
for handsfree operations**

**Water Resistant**

**Unconditional Replacement Warranty  
of 2 years on radio and  
1 year on accessories (battery & charger)**

# Talk PRO™ X-10



Port for handsfree  
accessory connector

Battery Lock



Push-To-Talk (PTT)  
Button

Volume +

Volume -



Fail-proof Rugged  
Antenna Design

Charging Port

Monitor Button  
Enables weak signals  
to be heard clearly

Rugged and unbreakable  
radio holster with  
additional bottom support

## General Features

- 446MHz License Free Band
- With Govt. Equipment Type Approval (ETA)
- BIS Certification Battery
- 48 hours Talk Time
- Battery Life of Over 2 years
- Range of 2kms
- 750 mW Speaker for Loud Audio
- Easy Fit Radio Holster



## SPECIFICATIONS

# Talk PRO<sup>™</sup> X-10

### General

Frequency Range	UHF:446-446.2MHz
Channel Capacity	16
Channel Spacing	25KHz/12.5KHz
Operating Temperature	-20°C~+60°C
Antenna Impedance	50Ω
Operating Voltage	DC 3.7V(±20%)
Battery Capacity	2300 mAh
Frequency Stability	≤ ± 2.5ppm
Dimensions	58(L)*33.5(W)*155(H)mm
Weight	141g(including battery pack)

### Transmitter

Power Output	≤ 2W
Modulation	11KøF3E/16KøF3E
Rated Audio Distortion	≤ 5%
Adjacent Power	60dB
Modulation Limitation	≤ 5KHz(Wide)/2.5KHz(Narrow)

### Receiver

Sensitivity	≤ -123dBm (12dB SINAD)
Adjacent Selectivity	≥ 60dB(Wide)/55dB(Narrow)
Intermodulation Rejection Ratio	≥ 60dB(Wide)/55dB(Narrow)
Spurious Suppression	≥ 60dB(Wide)/55dB(Narrow)
Rated Audio Output Power	750mW
Rated Audio Distortion	≤5%



## ACCESSORIES

### Standard Accessories



Adaptor



USB Cable



Belt Clip



Battery



Hand Strap

### Optional Accessories



Earpiece



Programming Cable